



Horse Stable Manure Management

G-97

Eileen Wheeler, Assistant Professor
 Jennifer Smith Zajackowski, Senior Research Technologist



Manure handling is a necessary evil of stable management with horse owners naturally preferring to ride rather than clean stalls. Making sure that stall cleaning and other manure handling chores are done efficiently will lead to more available time with the horse. It is important to recognize that horses produce large amounts of manure that quickly accumulates! About 12 tons of manure and soiled bedding will be removed annually from each horse stall (housing a full-time occupant). Careful consideration of how this material is moved and stored is needed for efficient manure management. Getting the manure out of a stall is only the beginning. A complete manure management system involves collection, storage (temporary or long-term), and disposal or utilization. This publication provides information to stable managers on horse manure characteristics and options for its

movement and storage. Associated issues such as odor control, fly breeding, and environmental impact are addressed in relation to horse facilities.

Manure management practices within horse facilities deserve careful attention. Since most horses are kept in suburban or rural residential settings, it is essential for stables to be good neighbors. Often, suburban horse facilities have limited or no acreage for land disposal of manure and soiled bedding. There are several alternatives for handling manure that include land disposal, stockpiling for future handling, removal from stable site, and composting. Some stables have developed markets to distribute or sell the stall waste. Whether in a suburban or rural setting, proper manure management is based on simple principles that will virtually eliminate environmental pollution impacts and nuisances such as odor and flies.




Table of Contents . . .

Stall Waste Production and Characteristics	2
Environmental Impact	5
Minimizing Nuisances	5
Preventing Water Pollution	6
Manure Handling	7
Manure Storage	9
Construction of the Manure Storage	11
Siting the Manure Storage	14
Management of the Stored Manure	14
Vegetated Filter Area	13
Manure Disposal	15
Other Stable Wastes	17
Keeping it Legal	18
Have a Plan	18
Summary	18
Additional Resources	19

Stall Waste Production and Characteristics

Manure includes both the solid and liquid portions of waste. Horse manure is about 60% solids and 40% urine. On average, a horse produces 0.5 ounces feces and 0.3 fluid ounces urine per pound of body weight every day. A 1000-pound horse produces about 31 pounds of feces and 2.4 gallons of urine daily, which totals around 51 pounds of total raw waste per day in feces and urine (Figure 1). Soiled bedding removed with the manure during stall cleaning may account for another 8 to 15 pounds per day of waste. The volume of soiled bedding removed equals almost twice the volume of manure removed, but varies widely depending on management practices. So for each stall, about 60 to 70 pounds of total waste material is removed daily. This results in about 12 tons of waste a year per stall with 8.5 tons being manure from a 1000-pound horse. The density of horse manure is about 63 lb/ft³. Therefore, 51 pounds of manure would occupy about 0.81 cubic feet. The soiled stall bedding removed with this manure (feces and urine) would be about twice this volume, so the total volume of stall waste removed per day per 1000 pound horse may be estimated as 2.4 ft³. To put all these numbers in perspective, annual stall waste from one horse would fill his 12' x 12' stall about 6-feet deep (assumes no settling). Plan now for handling this material!

Barn chores include a daily cleanout of manure and soiled bedding. This leads to a steady stream of manure material to handle. There are several common stall bedding materials and each has different






Figure 1. Average manure and urine created by a 1000 lb. horse.

Table 1. Approximate water absorption of dry bedding materials (typically 10% moisture).

Source: *Livestock Waste Facilities Handbook*, MWPS-18.

Material	pound water absorbed per pound bedding
Wheat straw	2.2
Hay- chopped mature	3.0
Tanning bark	4.0
Fine bark	2.5
Pine chips	3.0
Pine sawdust	2.5
Pine shavings	2.0
Hardwood chips, shavings, sawdust*	1.5
Corn shredded stover	2.5
Corn ground cobs	2.1

Not recommended for horse stall bedding: flax straw; oat straw; black cherry and walnut wood products.

The horse may eat oat straw.

* Walnut shavings cause founder so all hardwood shavings are often avoided as horse stall bedding on the chance that some walnut shavings would be mixed in.

Table 2. Hay and bedding material density.

Source: *Livestock Waste Facilities Handbook*, MWPS-18.

Form	Material	Density lb/ft ³
Loose	Alfalfa	4
	Non-legume Hay	4
	Straw	2 - 3
	Shavings	9
	Sawdust	7- 12
	Sand	105
Baled	Alfalfa	8
	Non-legume Hay	7
	Straw	5
	Wood Shavings 20	
Chopped	Alfalfa	6
	Non-legume Hay	6
	Straw	7

characteristics in handling, field application, suitability to composting and acceptance for sales. Availability and cost of bedding materials in the stable area will probably have the greatest influence on bedding selection. [See bedding characteristics Tables 1 and 2].

The manure management needs of pastured horses are different than stabled horses. The field deposited manure is beneficial as it serves a fertilizer function. Substantial amounts of manure can accumulate where horses congregate around gates, waterers, favorite shade areas, feeders and shelters. There should be weekly clean up in areas of heavy manure deposition for better pasture management, parasite control, and to diminish fly breeding. Manure collected from paddocks and pastures may be added to the stall waste stockpile.

Horse manure has been considered a valuable resource rather than a “waste”. Fertilizer value of the 8 1/2 tons of manure produced annually by a 1000-pound horse is about 102 pounds of nitrogen, 43 pounds of P₂O₅ (phosphorus pentoxide [phosphate] = 43.7% P) and 77 pounds of K₂O (potash = 83% K). The nutrient content of horse manure can also be represented as 12 lb/ton of N, 5 lb/ton of P₂O₅, and 9 lb/ton of K₂O (nutrient values for any manure vary widely so these are only guidelines). Traditionally, nitrate-nitrogen is the component that presents the most pollution potential due to its ability to move freely in the soil. Most of manure’s nitrogen is contained in the urine.

These characteristics are average values for horse manure (urine and feces). With the large amount of bedding material mixed with manure in typical stall waste, the fertilizer nutrient value would be different (see Direct Disposal section).




Figure 2. Farm plan showing manure management considerations for minimizing nuisances.

Environmental Impact

Minimizing Nuisances

For a suburban setting, overcoming potential problems includes overcoming perceptions and misconceptions about the nuisance and pollution potential of horse facilities. Most people enjoy horses, yet neighbors can be more concerned that horses are manure-generating, fly and odor machines. The operation of a horse facility with a large number of horses on limited acreage can intensify nuisance problems not noticed at small stables. Generally in the northeast, two to three acres of good pasture per horse is needed for summer feeding purposes. More horses per acre are common and successfully managed with supplemental feeding. Fortunately careful management and attention to detail can overcome potential problems of intensive horse operations. Pests commonly associated with animal agriculture are flies and small rodents, such as mice and rats. Flies and odors are the most common complaints. Proper manure management practices can virtually eliminate farm pests and odors. Figure 2 shows some simple yet important site planning features to minimize nuisances associated with manure management.

Insects. It is always easier and more effective to prevent fly breeding than it is to control adult flies. Eliminating the habitat required by the larvae to hatch and grow significantly reduces fly populations.




Figure 3. Preventing fly breeding is more effective than trying to control adult flies.

Flies deposit eggs in the top few inches of moist manure which means that minimizing the amount of moist manure surface area available to the fly is one fly reduction strategy. Eggs can hatch in as little as seven days under optimal temperature and moisture conditions. Fly breeding season starts when spring temperatures get above 65°F and ends at the first killing frost in the fall. It has been calculated that, under ideal breeding conditions, one fly can produce 300 million flies in about 60 days! If manure is removed from the stable site or made undesirable for fly breeding within a maximum seven-day cycle, few flies will develop.

Make manure less desirable as a fly egg deposition site by keeping it as dry as possible; below 50% moisture. Spread manure out in thin layers, during field application or field dragging, or exclude precipitation by roofing or tarping the permanent holding area and covering any dumpsters or temporary manure storage. Cleaning up decaying organic material is essential to fly control. Filth flies lay eggs in any decaying organic matter including spilled feed, manure left in stall corners, grass clippings, and manure piles. Store small amounts of manure in containers with tight fitting lids. Keeping spilled grain cleaned up will not only suppress filth fly populations but also reduce feed sources for mice and rats. Further information is available in *Pest Management Recommendation For Horses* (see Additional Resources).

Rodents. Clean out trash, dumps, piles of old lumber or manure, and garbage where rats and mice hide. Keeping weeds trimmed around buildings likewise reduces hiding places. Stacked feedbags create ideal




Figure 4. Clean tidy surroundings and secure feed storage will discourage rodents. Consider a hungry barn cat too.

passageways in which rodents can eat, hide, and breed. Store feed in rodent proof bins, preferably metal or lined with metal or wire mesh. A 30-gallon trash can will hold a 100-pound sack of feed. Feed from these containers rather than from an open bag, and clean up any spilled feed immediately. Areas under feed bins, bunks, and buckets are excellent feeding grounds for rodents. Concrete floors and foundations deter rodent entry as do metal shields on door and screens over small openings. Young mice can squeeze through an opening as small as one-quarter inch. Overfed, pet cats are not usually good mousers but a barn cat can deter rodents. Poison bait is not often safe around horse facilities due to the presence of pets and children, however secure bait boxes are effective.

Odor. Nuisance odor from the horses themselves is generally minimal. Offensive odors can be generated from manure. If manure is allowed to decompose without enough oxygen it will be anaerobic (without oxygen) and will usually produce offensive odors. Aerobic (with oxygen) decomposition, such as composting, does not produce such odors because the microbes decomposing the waste utilize the nutrients and produce odor-free compounds (water vapor and carbon dioxide, for example) as a by-product. It is best to anticipate some odor from the manure storage area due to daily fresh manure additions. Place the area downwind of the stable facility and residential areas to minimize odor problems. Summer breezes are the main concern if winter and summer prevailing wind directions are not the same. When odors are allowed to become a problem, neighbors will be less tolerant during warm weather as they are outdoors more often and have open house windows.

Aesthetics. Another nuisance associated with waste management can be the visual aspect of large manure storage piles. Keep the storage site screened from view with vegetation, fencing and/or by location in a visually remote area. A well-designed and managed stall waste facility can be reasonably contained and not offensive visually. Visually screening the storage is worthwhile because “out of sight is out of mind” if the storage is otherwise well managed.

Preventing Water Pollution

Manure Pile Runoff. Any on-site manure storage should not contribute to ground or surface water pollution. Leachate is the brownish liquid that has “leached” from the solid pile contents and drains off a waste pile bottom. Not all piles will have leachate;

in fact, manage to avoid leachate formation. Stall waste is typically very dry with little leachate. When water or pure manure, such as from paddock or arena cleanup, is added, some leachate may form. A covered storage area will have much less leachate than one exposed to precipitation. Make sure that any pile leachate is prevented from contaminating groundwater or nearby waterways by capturing or diverting it. A concrete pad with sidewalls will be necessary to contain leachate from very large uncovered piles. Leachate drainage to a treatment system such as a grassed infiltration area (see Vegetated Filter Area sidebar) will be necessary, especially for geologically and socially sensitive areas where runoff is a concern.

Another potential source of water pollution is from field-applied manure that is subject to surface runoff conditions or is deposited near waterways. Apply stall manure so that runoff is minimized. Guidelines are provided in the Direct Disposal section.

Stall Flooring. The type of stall flooring may determine the potential for groundwater pollution from the stable. Concrete, most asphalt, and well-packed clay floors are considered impermeable to water flow. However, with any stall flooring material, there is so much bedding used in horse stalls that urine and any liquid from the manure are soaked up by bedding. Therefore, free urine in contact with the flooring material is minimal compared to other livestock housing. Drains are not necessary in horse stall floors, except under circumstances noted below.

Floors in wash stalls will need to have impermeable and durable floors such as concrete or asphalt. Drains are recommended for wastewater removal to an approved discharge area (see Vegetated Filter Area sidebar). Some situations demand that stalls are frequently washed down and disinfected, such as foaling stalls or hospital stalls. When large amounts of water are used, impervious floors and drains will be necessary.

If drains are located in the stall, they should be outfitted with a removable cover and located to one side of the stall to prevent uncomfortable conditions when the horse lies down in the center of the stall. The floor should slope slightly (1-inch per 6-feet is adequate) toward the drain. An alternative is to slope the stall floor toward the front stall door where a shallow, narrow gutter (about 1-inch deep by 4 to 12 inch wide) is positioned along the front stall wall in the aisle floor. This gutter would then slope along the aisle toward drains. *Horse Stable Flooring Materials and Drainage* [G-96] has more information.

The floor in an open-sided shed is usually of the native material found on the building site. Pastured horses do not spend much time in the shelter unless encouraged to do so by feeding or fencing. Ground-water pollution potential is minimal because little manure will be deposited in the shed. If horses will be fed or confined in this facility, then a more durable floor may be desirable along with a plan to collect and dispose of the accumulated manure. Packed limestone screenings work very well in open sheds by providing good drainage and ease of cleaning.

Rainy-Day Paddocks. Many farm managers have rainy-day paddocks that are exercise lots with no pasture grass. They are used for turnout during inclement weather when horse traffic on grass pastures would tear the turf into a muddy mess. Ungrassed paddocks also work well for horses kept on limited acreage or when pastures have been reseeded, fertilized, or are rested as part of rotational grazing program. Some managers use outdoor riding arenas for turnout paddocks. Locate exercise paddocks on high ground with provision for cleaning the area of manure and decreasing runoff potential

(Figure 2). A stone dust footing works well by decreasing mud potential, aiding drainage, and providing a surface from which to pick manure. The rainy-day paddock should be surrounded by well-established sod so that any runoff is captured and diverted from adjoining buildings and pastures. Fencing of sensitive areas such as around streams and natural waterways will alleviate further water pollution. Please see the *Fencing for Horses* bulletin [G-98] for further detail on stream bank fencing and rainy-day paddock construction.

Manure Handling

Efficient Movement. When handling large quantities of bulky material, straight-line movement through wide doors is the most efficient. Avoid stable designs that necessitate turns and tight passages for travel from the stall to manure deposition area. Hand labor is most common in horse stall cleaning. To increase worker efficiency provide plenty of stall light, minimize lifting, and make the temporary manure stockpile area easily accessible from all areas of the stable (Figure 5).




Figure 5. Efficient handling of large quantities of bulky material includes straight-line movement through wide doors to a convenient stockpile area.

In most stables, stalls are cleaned daily and manure temporarily stockpiled in an accessible deposition area near the barn. To avoid additional handling, the temporary stockpile can be accumulated in a vehicle used for transport, such as a manure dumpster or spreader. Once the stall cleaning chores are finished or the temporary storage is filled, the stockpile is moved to the longer-term storage location or removed from the stable site.

Mechanization can replace some hand labor of stall cleaning. A common adaptation is a motorized vehicle pulling a cart through the working aisle of the stable. The numerous repositionings of the cart and engine exhaust from this method can detract from its ultimate usefulness and become a health hazard if the stable is inadequately ventilated. The cart can efficiently transport material to areas more remote from the stable.




Figure 6. Automated barn cleaner. [Adapted from *Livestock Waste Facilities Handbook*, MWPS-18.]




Figure 7. Options for automatic barn cleaner gutter and stockpile placements.

A mechanized alternative is the barn cleaner which automatically moves the waste from the stall area to the temporary stockpile area. A barn cleaner is a scraper that operates in a narrow gutter (about 16-inches wide) and has closely spaced flights on a chain drive (Figure 6). It is designed to handle wastes with high solids content typical of horse stall waste. The gutter cleaner can be located under the floor at the back of the stall or along the side of an aisle servicing the stalls (Figure 7). The primary advantage is that minimal worker effort is required to move stall waste into the gutter: no lifting, no moving carts, and no travel to the temporary stockpile area. The disadvantages are the initial cost, complexity of installation, and maintenance of the gutter system. Stall gutters must be covered and bedded over when horses are in the stall. With aisle gutters, horses get used to stepping around them even if gutters are left uncovered. Safety may become an issue if normally covered aisle gutters are left open.

Manure Storage

The stall waste will have to be stored somewhere whether temporarily or longer term. Stored manure must be kept in a fly-tight area during the warm months or managed to prevent fly breeding and protected from rainfall and surface runoff. A well-built storage pad or container will aid waste handling and minimize pollution potential from the pile. The pad can be as informal as a level, well-packed surface with a wood or masonry backstop (Figures 8, 9, 10) or can be a covered structure with impermeable flooring. If topography permits, a below-grade storage container is a less objectionable structure as it keeps the manure contained to a small area, is out of view, can be covered, and is easily filled using gravity to dump waste into it (Figure 11). One side should be at ground level for emptying. Longer-term manure storages are often more substantial structures than short-term storages. Large quantities of manure require a storage designed with wide door(s), a high roof, and strong construction to allow cleanout with power equipment. Examples of features are shown in Figures 12 and 13. Additional details of large manure storages are available in the *Livestock Waste Facilities Handbook* (see Additional Resources). Manure for commercial pick up can be stored in a container or dumpster. With any manure storage, large or small, a tarp or other cover is recommended to minimize leachate production from rainfall.




Figure 8. Simple manure stockpile pad, with backstop, that is suitable for a small stable. It is recommended that a tarp or other cover be used to minimize leachate production from precipitation.




Figure 9. Manure pad slope and drainage. Drain and gutter are recommended in all cases. They are essential if the manure stack will not be protected from rainfall. Leachate (effluent) must be directed to a storage tank and/or suitable method of disposal. [Reproduced with permission from *Livestock Waste Facilities Handbook*, MWPS-18.]






Figure 10. Bucking wall options. Note: These drawings are general representations and are not meant as construction drawings. A site-specific design is recommended in all cases. If soil backfill is to be placed behind the wall, a more economical wall may be possible. [Adapted from *Livestock Waste Facilities Handbook*, MWPS-18.]

Construction of the Manure Storage

Size the storage for about 180 days of long-term storage in cold climates. This provides winter storage when fields are not accessible and for summer when crops may be present. An estimated waste production of 2.4 ft³ per day per horse would require 432 ft³ of storage for each stalled horse. Base sizing figures on estimates that reflect the specific stable's management. It is better to have a slightly large storage facility than one that is too small. Whether a simple manure pad or more formal storage structure, some common construction practices will minimize labor and make nuisance control easier.

Slope entrance ramps upward with a minimum 10:1 slope (Figure 9) to keep out surface water. Provide a rough-surfaced, load-out ramp at least 40-feet wide if commercial sized-agricultural machinery will be used to load and unload the storage. A smaller width of 20-feet is acceptable for smaller farm and garden tractors. This leaves room to maneuver the tractor during unloading. Angle grooves across the ramp to drain rainwater. Install a 4-inch thick concrete floor and ramp over

6-inches of coarse gravel or crushed rock (up to 1-1/2 inch aggregate size). Two inches of sand can replace gravel as fill under the concrete when placed over undisturbed or compacted soil. Smaller or private stables can suffice with well-packed stone dust. Bucking walls (backstop) are recommended to aid in unloading. Bucking wall options are provided in Figures 10 and 12.

If liquids such as unabsorbed urine, snowmelt, and rain, are to be retained in the storage, slope the floor toward a closed end. The floor may be sloped to one or both sides, with openings on the low side to a gutter or surface drain (Figures 9 and 13). Unabsorbed liquids may be diverted to a gently sloped, grassed area that acts as a vegetated filter (Figure 14). Additional problems of handling separated liquids may make use of roofs or extra bedding a better solution. A large unroofed storage (such as those serving multiple stables at a track) may need floor drains connected to underground corrosion resistant 8-inch pipe to carry away liquids. Provide removable grills for periodic cleaning, or start the stack with 6-inches of absorbent material such as wood or bark chips to absorb some liquids and permit the rest to drain.




Figure 11. Manure storage container utilizes topography and gravity for ease of waste handling chores.




Figure 12. Features of large, roofed, solid-manure storage.




Figure 13. Covered storage with leachate collection for wet materials.

Vegetated Filter Area.

A grassed, gently sloped area may be used as a filter and infiltration area for wastewater (Figure 14). Wastewater is piped to the filter area, spread evenly across the top portion of the filter, and as it flows through the soil profile and down the slight slope, biological activity and adsorption in the soil matrix removes waste materials. Most biological activity occurs in the topsoil layer where aerobic (using oxygen) activity provides for odor-free treatment. Obviously, not all soils are equally suitable as some provide rapid infiltration for limited treatment while others are rather impermeable and provide surface run-off. Frozen soil will not act as a proper filter. Get professional help (Natural Resources Conservation Service, County Conservation District, for example) for proper filter sizing and design.

Vegetated filter area is a relatively low-cost farm wastewater treatment system. They can be variable in cost, approaching that of a septic system. In size, one rule of thumb is to provide about 10-square feet of vegetated filter for each gallon of wastewater being handled. The spreading device at the head of the filter strip is important for establishing even flow to minimize short-circuiting wastewater through the area. A settling tank prior to the filter strip will be needed if manure solids are allowed into the wastewater.

Vegetated filter areas need to be well vegetated before put to use. Animals need to be kept off the filter strip, as the frequently wet conditions of the soil will lead to destruction of the sod cover by horse grazing and exercise. If the storage facility will hold the manure from more than a few horses, the volume and strength of the leachate may be too great to send directly to a vegetated filter. In that case, the liquid should be collected in a tank and be dosed to the vegetated filter every three or more days, or be irrigated on pasture. In any case, a site-specific design is recommended.




Figure 14. Grassed filter area for treating manure storage leachate. Use a site-specific design of the vegetated filter based on leachate production and site characteristics.

Siting the Manure Storage

The waste stockpile areas must be accessible to trucks or tractors in all weather conditions. A location on high ground will usually provide firm soil well above ground water. This will be a suitable base for the storage facility and access road. Keep manure away from building materials, as corrosive chemicals in the manure can damage them. Do not store manure in places where runoff or floodwater will cause nutrients to enter nearby waterways. Table 3 lists distances to separate the manure storage from sensitive areas such as nearby water sources or residences. Do not store manure in paddocks due to increased parasite exposure for the horses. Locate storages downwind from both the farm and neighbors' residences. Consider the aesthetics of the storage placement so that it can be screened from view (Figure 2). Use natural or man-made screening such as a hedgerow or fence to improve the aesthetics and help contain any odors. Remember that for many perceived nuisances, out of sight can be out of mind for neighbors. Provide for easy filling of the storage with a tractor-mounted manure loader or scraper-elevator stacker unit (Figures 6 and 11). Unload waste with a tractor-mounted bucket.

Good drainage at any manure storage site is absolutely necessary. The site may be graded to divert surface runoff without creating erosion. Poor drainage results in saturated conditions leading to muddy access and pools of dirty water. Divert any surface drainage water and runoff from nearby roofs away from the pile area. *On-Farm Composting Handbook*, NRAES-54 has detail of surface water

diversion and site grading. Many stables and indoor riding arenas do not have gutters and downspouts so that runoff from these buildings is substantial. A gutter and downspout system will collect and divert water away from the building foundation and bypass the manure storage. Tarps or a roofed structure over the manure storage can be used to minimize rainwater entry if leachate containment becomes a problem. Do not allow polluted runoff to pool as mosquitoes and flies will breed in the moist area.

Management of the Stored Manure

With proper management, the nuisances of flies and odors from manure storage can be minimal. The major deterrent to fly breeding in horse operations is to keep the manure as dry as possible. Other wet organic material sites also need to be removed. Remove manure from the farm at least every seven days during fly breeding season or operate a properly managed composting facility.

Add new stall waste to the pile as a large block of material to minimize fresh manure surface exposure. This reduces the area of odor volatilization and access to moist manure for fly breeding. Avoid dumping new material on top of a pile where it spreads out and falls away down the sides creating a large fresh, wet manure surface area promoting flies and odor. Flies lay eggs in the top two inches of moist manure.

Beneficial and naturally occurring fly predators (tiny, non-stinging wasps) and parasites should be associated with the manure storage. Avoid indiscriminate use of larvicides and other pesticides that

Table 3. Minimum separation distances commonly recommended for composting and manure handling activities. Source: *On-Farm Composting Handbook*, NRAES-54.

Sensitive area	Minimum separation distance (feet)
Property line	50 - 100
Residence or place of business	200 - 500
Private well or other potable water source	100 - 200
Wetlands or surface water (streams, pond, lakes)	100 - 200
Subsurface drainage pipe or drainage ditch discharging to a natural water course	25
Water table (seasonal high)	2 - 5
Bedrock	2 - 5

kill predator wasps and parasites. Depending on wasp species, they have a 10 to 28 day egg and larva stages. Wasps are active during fly season (some are killed by cold temperatures) and their activity depends on manure conditions with dry manure best. Wet manure decreases wasp effectiveness.

When cleaning out the storage, it is best to leave a 4-inch DRY pad of manure over the bottom of the storage area to provide a stock of fly parasites and predators. Manure removal can be staggered to leave one section per week to supply fly predators and parasites. Remove a winter's stockpile of manure during cold weather (<65°F) before fly breeding begins.

Manure Disposal

Direct Disposal. Direct disposal involves the on-farm use of the stall waste via field application. Proper field application demands equipment such as a tractor and spreader so that the manure is applied in a thin layer over the soil. The thin layer is essential for

drying of the manure to discourage fly breeding. It also spreads the nutrients for more optimal plant use. Weekly spreading in the summer months will disrupt fly breeding and egg development cycles. To minimize pollution from runoff, it is best not to spread manure on frozen ground or near waterways. It may not be possible to spread manure each week, year-round, in which case the manure must be stockpiled. In cold climates, figure on 180 days of stockpile storage space. Timing of application may be limited to preplanting and postharvest dates for cultivated fields. Fields may not be accessible due to heavy snow accumulation or soil that is too wet to support equipment traffic.

Spreading manure in thin layers has been thought to reduce parasite numbers by desiccating the eggs. This does hold true under dry and extreme cold or hot conditions. Under the moist conditions encountered in the northeastern United States the practice of spreading manure in thin layers on pasture is being questioned (as far as parasite control is concerned;




Figure 15. Proper application with a tractor and spreader provides a thin layer of stable waste over the soil to improve manure drying and fertilizer application along with decreased fly breeding.

Adapted from *On-Farm Composting Handbook*, NRAES-54.

the other nutrient, aesthetic, and fly egg desiccation characteristics remain). There is some recent evidence that spreading thin layers of manure on pastures can enhance grazing horses' parasite exposure by spreading viable parasites over a larger area. The recommendation is to leave the manure piles in clumps and pick them up for disposal outside the pasture area.

Field application is based on fertilizer needs of the crop or pasture grass through soil sampling. The approximate fertilizer value of manure from bedded horse stalls (46% dry matter) is 4 lb/ton ammonium-N, 14 lb/ton Total N, 4 lb/ton P_2O_5 (phosphate) and 14 lb/ton K_2O (potash). [Fertilizer value of manure at 20% moisture without bedding is approximately 12-5-9 lb/ton (N- P_2O_5 - K_2O)]. Nutrient values vary widely so use these values as guidelines and have the manure analyzed if more specific analysis is needed. The amount of organic nitrogen mineralized (released to crops) during the first cropping season after application of horse manure is about 0.20. Organic nitrogen must be released through mineralization before plants can use it. About 20% of the organic N from horse manure is available to the pasture grass the year of application. Organic N released during subsequent seasons is usually about 50% (second year), 25% (third year) and 13% (fourth year) of the first year mineralization.

Contract Disposal. Another manure disposal option is to contract with a hauler who will remove the waste from the stable facility. The waste can be used in a commercial composting operation or for other functions where the waste disposal is the responsibility of the hauler. Dumpsters are positioned at the stable for temporary stall waste storage (no trash or garbage); a full dumpster is replaced with an empty one. Dumpsters should be sized so that the contents are emptied at least weekly during the fly breeding season. Make sure the dumpster is located so that barn waste can be conveniently dumped into it and trucks can access and empty the dumpster during all weather (Figure 11). A concrete tank or pad is useful to contain any dumpster leachate.

A less formal "contract" disposal is to interest neighbors in free garden organic material. The key is to locate the organic fertilizer enthusiasts. Owners of small stables have had success with newspaper ads and locating "free" bagged manure at curbside. Empty feed sacks filled with horse manure are a useful package for manure distribution.




Figure 16. Simple process of a composting stall waste pile.

By-Product: Compost. An alternative to "disposing" of horse manure is to compost it into a by-product of the operation. Composting occurs naturally if stall waste is allowed to decompose in the presence of oxygen and is kept relatively moist, above 50% moisture content (Figure 16). The microbes that decompose the bedding and manure are naturally occurring in stall waste. In fact, commercial composters and mushroom substrate preparation facilities often seek straw-bedded horse stall waste. Composting provides a material that is more readily marketable than raw stall waste. Finished compost is partially degraded manure and is more organically stable and therefore presents less of a pollution threat. Its finer texture, high organic matter content and fertilizer value make it desirable as a garden soil amendment. Composting reduces the volume of waste by 40% to 70%. Horse manure, with its associated bedding, is almost perfectly suited for composting because it has appropriate levels of nitrogenous material and carbon-based bedding material. (The carbon: nitrogen ratio of stall waste is 20:1 to 30:1.) Stables have successfully given away, or even sold, bulk and bagged horse compost. Golf courses and nurseries provide an outlet for truckloads of compost.

Pathogens and fly eggs are killed by composting's high temperature. Parasite eggs can be killed with 30-minute exposure to 140°F that will occur on the inside of a properly composted pile. These temperatures are not reached on the pile exterior which is one reason the pile is periodically mixed and turned so that exterior material is incorpo-

rated into the middle for full composting. Stall waste composts well in piles that are at least 3-feet square by 3-feet deep. Smaller piles will not retain enough heat to reach the proper composting temperature.

There is a trade off between the complexities of composting facilities versus the amount of time to produce finished compost. For example, static pile composting which is informally practiced at most stables, involves simply piling the stall waste and letting it “compost” for 6-months to 2-years. In contrast, with more ideal conditions and intensive management, the same stall waste could be composted in about four weeks. Intensive management of a composting operation entails daily monitoring and periodic (perhaps weekly) attention to mixing the raw ingredients, forming the pile and perhaps turning the compost (Figure 17). Compost microbes live most comfortably at certain temperatures (130-140°F) and moisture levels (50-60%). They must have oxygen (5-15%) so waste pile aeration is necessary. The more carefully these biological factors are controlled, the more sophisticated the compost facility becomes. It takes two weeks to six months to produce finished compost under professionally managed conditions. The benefit to producing it faster is that less space is needed for the compost processing and storage. Large, commercial compost facilities will provide near ideal conditions for composting in order to speed the process and



EFW/355

Figure 17. A front-end loader (pictured) or specialized compost turning equipment is used to turn compost in professionally managed composting facilities. Reproduced with permission from *On-Farm Composting Handbook*, NRAES-54.

minimize space use. A good and thorough *On-Farm Composting Handbook* is available (see Additional Resources).

Intensive composting will be another operation to be managed daily at the stable. This responsibility may not be of interest to all stable managers. The sale or disposal of the compost must also be considered. Marketing and potential liability becomes important if off-farm disposal is desired. Having a ready outlet for compost will make the facility and time investment more worthwhile. With limited hauling, a centralized cooperative facility could be managed for several farms with more effective process labor and marketing of compost being additional benefits.

Other Stable Wastes

Waste management is not confined to horse stall waste at a large facility. Keep trash separate from manure and soiled bedding for disposal purposes. Recyclable materials are also kept separated for collection. Medical waste (e.g. syringes) usually has special disposal requirements. Fertilizers and pesticides and their containers sometimes have restrictions on how they are disposed. Human waste from a bathroom requires a septic system or connection to municipal sewer. Gray water, such as shower and sink water, may also go to the septic/sewer unless there is benefit in diverting it for groundskeeping or other uses where high quality water is not necessary. A grassed filter area may be used to treat wastewater from the stable's horse wash stalls, tack area, laundry, showers, and feed room.

Drainage and surface runoff from pavement, building roofs, unvegetated paddocks, and exercise areas needs to be managed. This is especially important for areas where manure is allowed to accumulate between rainfall or thawing events. Runoff should not enter natural waterways where it could increase nutrient level of the water or contribute to increased erosion. Pick up excess manure from paddocks and exercise areas and add to manure handling system.

Keeping It Legal

Among state and federal agencies, there are various regulations for protecting environmental quality that are aimed at manure management. Often categories of livestock (which includes horse) operations are defined which relate to their potential to cause environmental harm. When stable facilities and manure storage structures are properly designed, constructed, and managed, the manure is an important and environmentally safe source of nutrients and organic matter. Proper land application of manure will not cause water quality problems. The intent of regulations is to ensure that economically practical technical techniques are used in all aspects of manure handling. All farms are required to properly handle manure in accordance with Pennsylvania's Clean Streams Law, but formal nutrient (manure) management plans are generally not required of all farms.

The Pennsylvania Nutrient Management Act is aimed at higher density livestock farms to address water quality concerns. The law defines the regulated community as those animal production facilities having more than two Animal Equivalent Units (aeu) per acre. An animal equivalent unit is 1000-pounds of animal, or about one horse or four market-weight hogs, etc. Although most horse facilities would be smaller in total animal equivalent units than the currently targeted Concentrated Animal Operations (CAO), stable owners should be aware of the regulatory emphasis being placed on environmental stewardship. (Currently a CAO has more than 1000 aeu or more than 301 aeu located in special protection watersheds). Be aware that many suburban horse farms are considered higher density livestock farms, according to the Nutrient Management Act guidelines, since they have more than two animal equivalent units per acre. Fact sheets of environmental information are available from the Pennsylvania Department of Environmental Protection (DEP) web page: www.dep.state.pa.us (choose Subjects, then Water Management). A more local source of conservation-minded assistance for manure management planning and design are county Conservation District and Natural Resources Conservation Service offices [see phone directory Blue Pages under County Government and United States Government (Agriculture), respectively].

Have a Plan

It is recommended that managers of large stables (10 or more horses) prepare a written manure management plan. This is a useful tool for the operator and shows that a proactive stance has been taken if methods of manure handling are questioned. Keep it simple but address exactly how and where manure is stored and disposed. Address leachate management and manure storage siting for reduction in water pollution potential. Address water run-on and run-off from the stable and storage site. Even the exercise of preparing a simple hand-written plan is beneficial in thinking through how to efficiently handle tons of manure and soiled bedding.

Summary

Making manure management a more thoughtful and efficient chore has benefit for both the horse owner and their neighbors. Time spent planning for proper and easy manure disposal will pay back in many more hours spent enjoying the horses through decreased time and effort in stall cleaning and manure disposal chores. Maintaining good neighbor relations through fly and odor minimization, will assure the compatibility of horse stables within the neighborhood.

Additional Resources

Livestock Waste Facilities Handbook. MWPS-18. 1985. 2nd edition. MidWest Plan Service. Iowa State University, Ames, IA 50011. (515) 294-4337, fax (515) 294-9589. www.mwpsHQ.org

On-Farm Composting Handbook. NRAES-54. 1992. R. Rynk, Editor. Natural Resources, Agriculture and Engineering Service, 152 Riley-Robb Hall, Ithaca, NY 14853-5701. (607) 255-7654. fax (607)254-8770 www.nraes.org

Pest Management Recommendations for Horses. P. Kaufman, D. Rutz and C. Pitts. Penn State Cooperative Extension, University Park, PA

The above titles are available from:

Publication Distribution Center
Pennsylvania State University
112 Agricultural Administration Building
University Park, PA 16802-2602
(814) 865-6713 www.pubs.cas.psu.edu

Acknowledgements

The authors thank the following experts in manure management and equine sciences for their outstanding technical advice offered during review of this manuscript:

Robert Graves

Professor, Agricultural and Biological Engineering

Patricia Comerford

Instructor, Dairy and Animal Science

Timothy Murphy

Conservation Engineer, Natural Resources
Conservation Service, NRCS Pennsylvania

Daniel Greig

District Manager, Chester County (PA)

Conservation District

PSU 4/01

Other titles in the Agricultural and Biological Engineering Horse Facilities series include:
Horse Stall Design Features, G-95
Horse Stable Flooring Materials and Drainage, G-96
Fencing for Horses, G-98
Horse Stable Ventilation, G-99
Fire Safety in Horse Stables, G-100
Riding Arena Footing Materials, G-101

For a copy of our fact sheet listing contact:
Pennsylvania State University
Agricultural and Biological Engineering Extension
246 Agricultural Engineering Building
University Park, PA 16802
(814) 865-7685, Fax: (814) 863-1031
www.age.psu.edu/dept/extension/index/html